

BP-N510 series

Compact-Size Box PC with Intel 11th Tiger Lake-U Series Processor for Ultra Low-Power Fanless Solution

Product Features

- 11th Gen Intel® Core™ i7/i5/i3 Tiger Lake U-series Processor
- SODIMM DDR4 memory up to 64GB
- Intel® HD Graphics Integrated graphic card
- HDMI+VGA Synch. or asynch. display
- 2 x Intel® GbE LAN
- 4 x RS232 / 2 x RS-232/485 Ports
- 4 x USB3.0/2.0 Port, 4 x USB2.0 Ports
- Easy to replace cooling fan



INTEL core i5 and INTEL core i7 SKU with samrt FAN

INTEL Celeron and INTEL core i3 SKU FAN Less BOX-PC



Specifications

Processor	CPU	Intel® 11th Core Intel Core i3 / i5 / i7 CPU
Memory	Architecture	Dual channel DDR4
	Capacity	Max. 64GB
	Socket	2 * DDR4 SODIMM
Display	Graphic Controller	Intel Integrated graphic card
	VGA	Max. resolution: 2K
	HDMI	Max. resolution: 4K
	Dual Display	HDMI+VGA Synch. or asynch. display
Ethernet	Controller	LAN1: Intel I219 GbE LAN LAN2: Intel I210 GbE LAN
Super I/O	Watch Dog Timer	0~255 sec., providing Watch Dog program.
	Controller	Support system temp. monitoring
Audio	Controller	Realtek HD ALC662_VDO_GR audio decoder (right & left channel + MIC)
	USB 3.0	4 x USB 3.0/2.0 PORTS
	USB 2.0	4 x USB 2.0 PORTS
I/O	Serial Port	Com1 9-wire RS232 TX/RX signal, support 4000V surge protection, DB9 port
		Com2 3-wire RS232 TX/RX signal, support 4000V surge protection, DB9 port
		Com3-COM4 3-wire RS232/RS485(optional), RS232 TX/RX signal, support 4000V surge protection, RS485 support 3KV isolation protection, DB9 port
		COM5-COM6 3-wire RS232 TX/RX signal, support 4000V surge protection, DB9 port
		GPIO
Expansion Bus	Mini-PCIe	1* Full-size Mini-PCIe socket, support PCIe & USB device
	UIM Socket	3G UIM Card socket
Storage	SATA	1* standard 7Pin SATA-III & power connector, transmission rate: max. 3Gb/s
	M-SATA	1* full-size Mini-PCIe socket, support m-SATA SSD, transmission rate: max. 3Gb/s
Power	Power Type	AT/ATX(optional), DC9-30V extended voltage input, support power reverse & over-voltage protection.
	Power Consumption	Support max. 50W
Other		POWER LED/HDD LED
		POWER Button
Environment	Operating Temp.	0° C ~ 60° C
	Storage Temp.	-40° C ~ 80° C
	Operating Humidity	0% ~ 90% relative humidity, non-condensing
	Storage Humidity	0% ~ 90% relative humidity, non-condensing
Formfactor	Dimensions	215 x 136 x 60mm
	Weight	1.5KG (Net weight)
Certificate		FCC, CE, RoHS

Industrial embedded system

Ordering Information

BP-N510-CL-6305	BP-N510-I3-1115G4	BP-N510-I5-1135G7	BP-N510-I7-1165G7
Intel® Celeron 6305 CPU, 1.8GHz · dual core dual thread, HDMI+VGA, 2 x Intel GbE LAN, 4 x Rs232 TX/RX signal, 2 x Rs232/RS485, 4 x USB3.0/2.0 Port, 4 x USB2.0 port, 1 x Mini PCIeX1, 1 x SATA, 1 x M-SATA, AC Adapter DC19V	Intel® 11th core i3 1115G4 CPU, 3.0GHz · dual core four thread · HDMI+VGA, 2 x Intel GbE LAN, 4 x Rs232 TX/RX signal, 2 x Rs232/RS485, 4 x SB3.0, 4 x USB2.0, 1 x Mini PCIeX1, 1 x SATA, 1 x M-SATA, AC Adapter DC19V	Intel® 11th core i5 1135G7 CPU, 2.4GHz · four core eight thread · , HDMI+VGA, 2 x Intel GbE LAN, 4 x Rs232 TX/RX signal, 2 x Rs232/RS485, 4 x USB3.0/2.0 Port, 4 x USB2.0 port, 1 x Mini PCIeX1, 1 x SATA, 1 x M-SATA, AC Adapter DC19V	Intel® 11th core i7 1165G7 CPU, 2.8GHz · four core eight thread · HDMI+VGA, 2 x Intel GbE LAN, 4 x Rs232 TX/RX signal, 2 x Rs232/RS485, 4 x USB3.0/2.0 Port, 4 x USB2.0 port, 1 x Mini PCIeX1, 1 x SATA, 1 x M-SATA, AC Adapter DC19V

Contact

Headquarters

16F-3, No. 258, Liancheng Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)

Malaysia office

2B-1, Tingkat Kenari 6, Taman Desa Ria, 11900 Bayan Lepas, Sungai Ara, Penang Malaysia
email: michael.yan@maincon.com.tw

Shanghai Office

Room 1901, No. 322, Xinda Building, Xianxia Road, Changning District 200051 Shanghai
email: david_huang@datavan.com.tw